

## WaStop® Access Technical Specification [ DN 125 mm ]

<b>Model no.</b>	WA125-425-2, WA125-425-3, WA125-425-4
<b>Nominal Size:</b>	125 mm
<b>Material</b>	
Manhole:	PE
Membrane:	Silicone MVQ
Fasteners:	Stainless steel (AISI 316)
Bracket:	Stainless steel (AISI 304)
Stainless steel frame:	EN1.4301

<b>Technical data:</b>	
Manhole size	425 mm
Riser	425 mm

Technical data:	Soft (S2)	Standard (S3)	Hard (S4)
Max. back pressure*:	3 m H <sub>2</sub> O	5 mH <sub>2</sub> O	8 mH <sub>2</sub> O
Horizontal opening pressure*:	160 mmH <sub>2</sub> O	193** mmH <sub>2</sub> O	216** mmH <sub>2</sub> O
Horizontal closing pressure*:	64 mmH <sub>2</sub> O	79** mmH <sub>2</sub> O	89** mmH <sub>2</sub> O
Submerged opening pressure*:	150** mmH <sub>2</sub> O	173** mmH <sub>2</sub> O	193** mmH <sub>2</sub> O
Submerged closing pressure*:	34** mmH <sub>2</sub> O	40** mmH <sub>2</sub> O	193** mmH <sub>2</sub> O

\* ) +/- 15%

- Values measured from bottom of pipe.

- Tests performed at room temperature (16-20 °C).

