

## WaStop® Inline Check Valve Technical Specification Stainless Steel AISI 304/316

<b>Model no.:</b>	N/A	WS1980-S3-304/316	N/A
<b>Nominal Size:</b>	80		
<b>Pipe:</b>	Stainless Steel AISI 304/316		
<b>Membrane:</b>	Polyurethane		
<b>Fasteners:</b>	Marine grade stainless steel (AISI 316)		

Technical data:	Soft (S2)	Standard (S3)	Hard (S4)
Max. back pressure*:	N/A ft H <sub>2</sub> O	16,4 ft H <sub>2</sub> O	N/A ft H <sub>2</sub> O
Horizontal opening pressure*:	N/A in H <sub>2</sub> O	29,3** in H <sub>2</sub> O	N/A** in H <sub>2</sub> O
Horizontal closing pressure*:	N/A in H <sub>2</sub> O	18,9** in H <sub>2</sub> O	N/A** in H <sub>2</sub> O
Submerged opening pressure*:	N/A** in H <sub>2</sub> O	13** in H <sub>2</sub> O	N/A** in H <sub>2</sub> O
Submerged closing pressure*:	N/A** in H <sub>2</sub> O	9,4** in H <sub>2</sub> O	N/A** in H <sub>2</sub> O
Vertical opening pressure*:	N/A** in H <sub>2</sub> O	N/A** in H <sub>2</sub> O	N/A** in H <sub>2</sub> O
Vertical closing pressure*:	N/A** in H <sub>2</sub> O	N/A** in H <sub>2</sub> O	N/A** in H <sub>2</sub> O

\*) +/- 15% \*\*) Modeled value  
 - Values measured from bottom of pipe.  
 - Tests performed at room temperature (61-68°F).

Max Flow	f/s	GPM
	16	201680

- Higher flows requires custom valve, contact Wapro  
 - Flange installation is highly recommended at flows above 6.5 f/s



In the submerged case opening pressure [mmH<sub>2</sub>O /inH<sub>2</sub>O] is the difference between the water level upstream and the water level downstream and in the open-air case to the invert of the pipe. In vertical applications, the vertical opening pressure is measured from the outlet of the WaStop.