

## WaStop® Access Technical Specification [ ]

<b>Model no.</b>	WS200-WA1000-S2, WS200-WA1000-S3, WS200-WA1000-S4
<b>Nominal Size:</b>	
<b>Material</b>	
Manhole:	PE
Membrane:	Silicone MVQ
Fasteners:	Stainless steel (AISI 316)
Bracket:	Stainless steel (AISI 304)
Stainless steel frame:	EN1.4301

Technical data:	
Manhole size	39,4"
Riser	39,4"

Technical data:	Soft (S2)	Standard (S3)	Hard (S4)
Max. back pressure*:	9,8 ft H <sub>2</sub> O	16,4ft H <sub>2</sub> O	26,2 ft H <sub>2</sub> O
Horizontal opening pressure*:	7,9 in H <sub>2</sub> O	9,8** in H <sub>2</sub> O	11,8** in H <sub>2</sub> O
Horizontal closing pressure*:	4,3 in H <sub>2</sub> O	4,7** in H <sub>2</sub> O	5,9** in H <sub>2</sub> O
Submerged opening pressure*:	4,5** in H <sub>2</sub> O	5,1** in H <sub>2</sub> O	5,7** in H <sub>2</sub> O
Submerged closing pressure*:	0,8** in H <sub>2</sub> O	1** in H <sub>2</sub> O	5,7** in H <sub>2</sub> O

\* ) +/- 15%  
 - Values measured from bottom of pipe.  
 - Tests performed at room temperature (61-68°F).

