

# WASTOP® PLASTIC SERIES

## WaStop 125 PVC

<b>Model Name</b>	WS125PVC
<b>Nominal Diameter</b>	NPS/OD 5
<b>Fasteners mtrl.</b>	AISI 316L
<b>Watertightness</b>	EN 13564
<b>Weight [lb]</b>	2.0
<b>Max. Flow Vel. [fps]</b>	6.6
<b>Max. Flow Vol. [GPM]</b>	301.2

## Product Variants

Art. No	WS125PVC-S2	WS125PVC-S3	WS125PVC-S4
<b>Valve Body mtrl.</b>	PVC	PVC	PVC
<b>Max. Back Pressure [ftH<sub>2</sub>O]</b>	9.8	16.4	26.2
<b>Horizontal Opening [inH<sub>2</sub>O]</b>	6.3	8.1	9.6
<b>Horizontal Closing [inH<sub>2</sub>O]</b>	3.0	3.3	3.3
<b>Submerged Opening [inH<sub>2</sub>O]</b>	5.5	5.5	7.1
<b>Submerged Closing [inH<sub>2</sub>O]</b>	0.6	0.6	1.0
<b>Vertical Opening [inH<sub>2</sub>O]</b>	9.1	9.1	10.9
<b>Vertical Closing [inH<sub>2</sub>O]</b>	4.7	4.7	5.7

