

# WASTOP® INLINE CHECK VALVE

## WaStop 690

<b>Model Name</b>	WS690
<b>Nominal Diameter</b>	DN 700
<b>Fasteners mtrl.</b>	EN 1.4404
<b>Gasket Mtrl.</b>	EPDM
<b>Weight [kg]</b>	73
<b>Min. ID Host Pipe [mm]</b>	692
<b>Max. ID Host Pipe [mm]</b>	710
<b>Max. Flow Vel. [m/s]</b>	4
<b>Max. Flow Vol. [l/s]</b>	1540

## Product Variants

Art. No	WS690-S2-304/316	WS690-S3-304/316	WS690-S4-304/316
<b>Membrane mtrl.</b>	Polyurethane	Polyurethane	Polyurethane
<b>Valve Body mtrl.</b>	EN 1.4301 / EN 1.4404	EN 1.4301 / EN 1.4404	EN 1.4301 / EN 1.4404
<b>Max. Back Pressure [mmH<sub>2</sub>O]</b>	3	5	8
<b>Horizontal Opening [mmH<sub>2</sub>O]</b>	215	265	280
<b>Horizontal Closing [mmH<sub>2</sub>O]</b>	135	170	175
<b>Submerged Opening [mmH<sub>2</sub>O]</b>	140	160	180
<b>Submerged Closing [mmH<sub>2</sub>O]</b>	40	45	60
<b>Vertical Opening [mmH<sub>2</sub>O]</b>	405	450	495
<b>Vertical Closing [mmH<sub>2</sub>O]</b>	245	275	300

