

# WASTOP® INLINE CHECK VALVE

## WaStop 750

<b>Model Name</b>	WS750
<b>Nominal Diameter</b>	DN 750
<b>Fasteners mtrl.</b>	EN 1.4404
<b>Gasket Mtrl.</b>	EPDM
<b>Weight [kg]</b>	90
<b>Min. ID Host Pipe [mm]</b>	755
<b>Max. ID Host Pipe [mm]</b>	767
<b>Max. Flow Vel. [m/s]</b>	4
<b>Max. Flow Vol. [l/s]</b>	1768

## Product Variants

Art. No	WS750-S2-304/316	WS750-S3-304/316	WS750-S4-304/316
<b>Membrane mtrl.</b>	Polyurethane	Polyurethane	Polyurethane
<b>Valve Body mtrl.</b>	EN 1.4301 / EN 1.4404	EN 1.4301 / EN 1.4404	EN 1.4301 / EN 1.4404
<b>Max. Back Pressure [mmH<sub>2</sub>O]</b>	3	5	8
<b>Horizontal Opening [mmH<sub>2</sub>O]</b>	305	365	450
<b>Horizontal Closing [mmH<sub>2</sub>O]</b>	190	220	270
<b>Submerged Opening [mmH<sub>2</sub>O]</b>	185	215	245
<b>Submerged Closing [mmH<sub>2</sub>O]</b>	60	70	90
<b>Vertical Opening [mmH<sub>2</sub>O]</b>	425	470	515
<b>Vertical Closing [mmH<sub>2</sub>O]</b>	180	200	220

