

WASTOP® PLASTIC SERIES

WaStop 75 PVC

Model Name	WS75PVC
Nominal Diameter	DN/OD 75
Fasteners mtrl.	EN 1.4404
Watertightness	EN 13564
Weight [kg]	0.3
Max. Flow Vel. [m/s]	2
Max. Flow Vol. [l/s]	9

Product Variants

Art. No	WS75PVC-S3	WS75PVC-S4	WS75PVC-C
Membrane mtrl.	MVQ Silicone	MVQ Silicone	EPDM
Valve Body mtrl.	PVC	PVC	PVC
Max. Back Pressure [mH ₂ O]	5	8	5
Horizontal Opening [mmH ₂ O]	250	280	285
Horizontal Closing [mmH ₂ O]	105	135	140
Submerged Opening [mmH2O]	150	180	190
Submerged Closing [mmH ₂ O]	60	90	110
Vertical Opening [mmH ₂ O]	225	255	260
Vertical Closing [mmH ₂ O]	60	90	100

WS75PVC-S3 Open Air 0.8 Submerged Outlet Without WaStop 0.7 0.6 Head loss [mH₂0] 0.5 0.4 0.3 0.2 0.1 0.0 0 2 8 6 4 Flow [//s]

© 2024 Wapro AB. This document is subject to copyrights owned by Wapro AB. Any amendments, republication, retransmission, and/or reproduction of all or any part of the document is expressly prohibited, unless the copyright owner of the material has expressly granted its prior written consent. All other rights are reserved

Wapro AB Munkahusvägen 103 SE-37431 Karlshamn +46 (0)454 185 10 wapro@wapro.com