

# WASTOP® INLINE CHECK VALVE

## WaStop 1185 Flange

<b>Model Name</b>	WS1185-FL
<b>Nominal Diameter</b>	DN 1200
<b>Fasteners mtrl.</b>	EN 1.4404
<b>Flange Pattern</b>	wapro
<b>Weight [kg]</b>	390
<b>Min. ID Host Pipe [mm]</b>	1193
<b>Max. ID Host Pipe [mm]</b>	1230
<b>Max. Flow Vel. [m/s]</b>	5
<b>Max. Flow Vol. [l/s]</b>	5654

## Product Variants

Art. No	WS1185-S3-FL-304/316	WS1185-S4-FL-304/316
<b>Membrane mtrl.</b>	Polyurethane	Polyurethane
<b>Valve Body mtrl.</b>	EN 1.4404 / EN 1.4301	EN 1.4404 / EN 1.4301
<b>Max. Back Pressure [mH<sub>2</sub>O]</b>	5	8
<b>Horizontal Opening [mmH<sub>2</sub>O]</b>	440	535
<b>Horizontal Closing [mmH<sub>2</sub>O]</b>	290	325
<b>Submerged Opening [mmH<sub>2</sub>O]</b>	265	300
<b>Submerged Closing [mmH<sub>2</sub>O]</b>	95	125

