

# WASTOP® INLINE CHECK VALVE

## WaStop 440

<b>Model Name</b>	WS440
<b>Nominal Diameter</b>	NPS 18
<b>Fasteners mtrl.</b>	AISI 316L
<b>Gasket Mtrl.</b>	EPDM
<b>Weight [lb]</b>	55.1
<b>Max. ID Host Pipe [in]</b>	18.3
<b>Min. ID Host Pipe [in]</b>	17.6
<b>Max. Flow Vel. [fps]</b>	9.8
<b>Max. Flow Vol. [GPM]</b>	7576.5

## Product Variants

Art. No	WS440-S3-304/316	WS440-S4-304/316
<b>Valve Body mtrl.</b>	AISI 304 / AISI 316L	AISI 304 / AISI 316L
<b>Max. Back Pressure [ftH<sub>2</sub>O]</b>	16.4	26.2
<b>Horizontal Opening [inH<sub>2</sub>O]</b>	9.1	20.5
<b>Horizontal Closing [inH<sub>2</sub>O]</b>	6.1	7.5
<b>Submerged Opening [inH<sub>2</sub>O]</b>	5.7	6.5
<b>Submerged Closing [inH<sub>2</sub>O]</b>	1.8	2.4
<b>Vertical Opening [inH<sub>2</sub>O]</b>	15.2	16.6
<b>Vertical Closing [inH<sub>2</sub>O]</b>	9.1	9.9

