

# WASTOP® INLINE CHECK VALVE

## WaStop 885

<b>Model Name</b>	WS885
<b>Nominal Diameter</b>	NPS 36
<b>Fasteners mtrl.</b>	AISI 316L
<b>Gasket Mtrl.</b>	EPDM
<b>Weight [lb]</b>	255.7
<b>Max. ID Host Pipe [in]</b>	35.9
<b>Min. ID Host Pipe [in]</b>	35.0
<b>Max. Flow Vel. [fps]</b>	13.1
<b>Max. Flow Vol. [GPM]</b>	40354.9

## Product Variants

Art. No	WS885-S2-304/316	WS885-S3-304/316	WS885-S4-304/316
<b>Valve Body mtrl.</b>	AISI 304 / AISI 316L	AISI 304 / AISI 316L	AISI 304 / AISI 316L
<b>Max. Back Pressure [ftH<sub>2</sub>O]</b>	9.8	16.4	26.2
<b>Horizontal Opening [inH<sub>2</sub>O]</b>	14.6	16.1	21.7
<b>Horizontal Closing [inH<sub>2</sub>O]</b>	9.4	10.6	13.4
<b>Submerged Opening [inH<sub>2</sub>O]</b>	8.5	9.6	10.8
<b>Submerged Closing [inH<sub>2</sub>O]</b>	2.8	3.1	4.1
<b>Vertical Opening [inH<sub>2</sub>O]</b>	17.9	19.9	21.9
<b>Vertical Closing [inH<sub>2</sub>O]</b>	10.8	12.0	13.3

