

# WASTOP® ACCESS

## WaStop Access DN160 WS160

<b>Model Name</b>	WS160-WA425
<b>Nominal Diameter</b>	DN/OD 160
<b>Bracket mtrl.</b>	EN 1.4404
<b>Chamber mtrl.</b>	PE
<b>Connection pipe</b>	160 PE
<b>Fasteners mtrl.</b>	EN 1.4404
<b>Plate mtrl.</b>	PVC
<b>Watertightness</b>	EN 13564
<b>Weight [kg]</b>	14

## Product Variants

Art. No	WS160-WA425-S2	WS160-WA425-S3	WS160-WA425-S4
<b>Membrane mtrl.</b>	MVQ Silicone	MVQ Silicone	MVQ Silicone
<b>Horizontal Opening [mmH<sub>2</sub>O]</b>	215	225	320
<b>Horizontal Closing [mmH<sub>2</sub>O]</b>	85	85	95
<b>Submerged Opening [mmH<sub>2</sub>O]</b>	155	180	190
<b>Submerged Closing [mmH<sub>2</sub>O]</b>	20	25	40
<b>Vertical Opening [mmH<sub>2</sub>O]</b>	235	265	290
<b>Vertical Closing [mmH<sub>2</sub>O]</b>	125	140	165

