

# WASTOP® INLINE CHECK VALVE

## WaStop 1040 Bell Bolt

<b>Model Name</b>	WS1040-BB
<b>Nominal Diameter</b>	DN 1050
<b>Fasteners mtrl.</b>	EN 1.4404
<b>Weight [kg]</b>	237
<b>Max. ID Host Pipe [mm]</b>	1070
<b>Min. ID Host Pipe [mm]</b>	1048
<b>Max. Flow Vel. [m/s]</b>	4
<b>Max. Flow Vol. [l/s]</b>	3464

## Product Variants

Art. No	WS1040-S3-BB-304/316	WS1040-S4-BB-304/316
<b>Membrane mtrl.</b>	Polyurethane	Polyurethane
<b>Valve Body mtrl.</b>	EN 1.4404 / EN 1.4301	EN 1.4404 / EN 1.4301
<b>Max. Back Pressure [mH<sub>2</sub>O]</b>	5	8
<b>Horizontal Opening [mmH<sub>2</sub>O]</b>	410	525
<b>Horizontal Closing [mmH<sub>2</sub>O]</b>	270	335
<b>Submerged Opening [mmH<sub>2</sub>O]</b>	265	300
<b>Submerged Closing [mmH<sub>2</sub>O]</b>	90	115

