

# WASTOP® INLINE CHECK VALVE

## WaStop 193

<b>Model Name</b>	WS193
<b>Nominal Diameter</b>	NPS 8
<b>Fasteners mtrl.</b>	AISI 316L
<b>Gasket Mtrl.</b>	EPDM
<b>Watertightness</b>	EN 13564
<b>Weight [lb]</b>	9.5
<b>Max. ID Host Pipe [in]</b>	8.2
<b>Min. ID Host Pipe [in]</b>	7.6
<b>Max. Flow Vel. [fps]</b>	6.6
<b>Max. Flow Vol. [GPM]</b>	1014.4

## Product Variants

Art. No	WS193-S2-316	WS193-S3-316	WS193-S4-316
<b>Valve Body mtrl.</b>	AISI 316L	AISI 316L	AISI 316L
<b>Max. Back Pressure [ftH<sub>2</sub>O]</b>	9.8	16.4	26.2
<b>Horizontal Opening [inH<sub>2</sub>O]</b>	8.3	9.3	12.4
<b>Horizontal Closing [inH<sub>2</sub>O]</b>	4.1	4.8	6.5
<b>Submerged Opening [inH<sub>2</sub>O]</b>	5.9	6.7	7.5
<b>Submerged Closing [inH<sub>2</sub>O]</b>	1.2	1.4	1.8
<b>Vertical Opening [inH<sub>2</sub>O]</b>	10.6	11.6	12.9
<b>Vertical Closing [inH<sub>2</sub>O]</b>	6.1	7.1	7.8

