

# WASTOP® PLASTIC SERIES

## WaStop 200 PVC

<b>Model Name</b>	WS200PVC
<b>Nominal Diameter</b>	DN/OD 200
<b>Fasteners mtrl.</b>	EN 1.4404
<b>Watertightness</b>	EN 13564
<b>Weight [kg]</b>	3.7
<b>Max. Flow Vel. [m/s]</b>	2
<b>Max. Flow Vol. [l/s]</b>	63

## Product Variants

Art. No	WS200PVC-S2	WS200PVC-S3	WS200PVC-S4	WS200PVC-C
<b>Membrane mtrl.</b>	MVQ Silicone	MVQ Silicone	MVQ Silicone	EPDM
<b>Valve Body mtrl.</b>	PVC	PVC	PVC	PVC
<b>Max. Back Pressure [mH<sub>2</sub>O]</b>	3	5	8	5
<b>Horizontal Opening [mmH<sub>2</sub>O]</b>	215	235	315	210
<b>Horizontal Closing [mmH<sub>2</sub>O]</b>	115	120	165	110
<b>Submerged Opening [mmH<sub>2</sub>O]</b>	150	170	190	170
<b>Submerged Closing [mmH<sub>2</sub>O]</b>	30	35	45	35
<b>Vertical Opening [mmH<sub>2</sub>O]</b>	270	295	325	295
<b>Vertical Closing [mmH<sub>2</sub>O]</b>	155	180	200	180

