

# WASTOP® PLASTIC SERIES

## WaStop 200 PVC

<b>Model Name</b>	WS200PVC
<b>Nominal Diameter</b>	NPS/OD 8
<b>Fasteners mtrl.</b>	AISI 316L
<b>Watertightness</b>	EN 13564
<b>Weight [lb]</b>	8.2
<b>Max. Flow Vel. [fps]</b>	6.6
<b>Max. Flow Vol. [GPM]</b>	998.6

## Product Variants

Art. No	WS200PVC-S2	WS200PVC-S3	WS200PVC-S4	WS200PVC-C
<b>Membrane mtrl.</b>	MVQ Silicone	MVQ Silicone	MVQ Silicone	EPDM
<b>Valve Body mtrl.</b>	PVC	PVC	PVC	PVC
<b>Max. Back Pressure [ftH<sub>2</sub>O]</b>	9.8	16.4	26.2	16.4
<b>Horizontal Opening [inH<sub>2</sub>O]</b>	8.5	9.3	12.4	8.3
<b>Horizontal Closing [inH<sub>2</sub>O]</b>	4.6	4.8	6.5	4.3
<b>Submerged Opening [inH<sub>2</sub>O]</b>	5.9	6.7	7.5	6.7
<b>Submerged Closing [inH<sub>2</sub>O]</b>	1.2	1.4	1.8	1.4
<b>Vertical Opening [inH<sub>2</sub>O]</b>	10.6	11.6	12.9	11.6
<b>Vertical Closing [inH<sub>2</sub>O]</b>	6.1	7.1	7.8	7.1

