

# WASTOP® INLINE CHECK VALVE

## WaStop 215

<b>Model Name</b>	WS215
<b>Nominal Diameter</b>	NPS 8
<b>Fasteners mtrl.</b>	AISI 316L
<b>Gasket Mtrl.</b>	EPDM
<b>Weight [lb]</b>	9.9
<b>Min. ID Host Pipe [in]</b>	8.5
<b>Max. ID Host Pipe [in]</b>	9.2
<b>Max. Flow Vel. [fps]</b>	6.6
<b>Max. Flow Vol. [GPM]</b>	1268.0

## Product Variants

Art. No	WS215-S3-316	WS215-S4-316
<b>Valve Body mtrl.</b>	AISI 316L	AISI 316L
<b>Max. Back Pressure [ftH<sub>2</sub>O]</b>	16.4	26.2
<b>Horizontal Opening [inH<sub>2</sub>O]</b>	7.4	13.4
<b>Horizontal Closing [inH<sub>2</sub>O]</b>	4.4	6.3
<b>Submerged Opening [inH<sub>2</sub>O]</b>	6.3	12.6
<b>Submerged Closing [inH<sub>2</sub>O]</b>	1.8	2.6
<b>Vertical Opening [inH<sub>2</sub>O]</b>	10.0	14.0
<b>Vertical Closing [inH<sub>2</sub>O]</b>	7.3	8.3

