

# WASTOP® INLINE CHECK VALVE

## WaStop 290

<b>Model Name</b>	WS290
<b>Nominal Diameter</b>	NPS 12
<b>Fasteners mtrl.</b>	AISI 316L
<b>Gasket Mtrl.</b>	EPDM
<b>Weight [lb]</b>	22.0
<b>Min. ID Host Pipe [in]</b>	11.5
<b>Max. ID Host Pipe [in]</b>	12.1
<b>Max. Flow Vel. [fps]</b>	9.8
<b>Max. Flow Vol. [GPM]</b>	3138.4

## Product Variants

<b>Art. No</b>	<b>WS290-S3-316</b>
<b>Membrane mtrl.</b>	EPDM
<b>Valve Body mtrl.</b>	AISI 316L
<b>Max. Back Pressure [ftH<sub>2</sub>O]</b>	16.4
<b>Horizontal Opening [inH<sub>2</sub>O]</b>	8.6
<b>Horizontal Closing [inH<sub>2</sub>O]</b>	5.2
<b>Submerged Opening [inH<sub>2</sub>O]</b>	5.7
<b>Submerged Closing [inH<sub>2</sub>O]</b>	1.8
<b>Vertical Opening [inH<sub>2</sub>O]</b>	13.2
<b>Vertical Closing [inH<sub>2</sub>O]</b>	7.7

