

WASTOP® INLINE CHECK VALVE

WaStop 390

| | |
|-------------------------------|-----------|
| Model Name | WS390 |
| Nominal Diameter | NPS 16 |
| Fasteners mtrl. | AISI 316L |
| Gasket Mtrl. | EPDM |
| Weight [lb] | 44.8 |
| Min. ID Host Pipe [in] | 15.5 |
| Max. ID Host Pipe [in] | 16.2 |
| Max. Flow Vel. [fps] | 9.8 |
| Max. Flow Vol. [GPM] | 5991.4 |

Product Variants

| Art. No | WS390-S3-316 | WS390-S4-316 |
|--|--------------|--------------|
| Valve Body mtrl. | AISI 316L | AISI 316L |
| Max. Back Pressure [ftH₂O] | 16.4 | 26.2 |
| Horizontal Opening [inH₂O] | 15.2 | 16.1 |
| Horizontal Closing [inH₂O] | 7.7 | 10.6 |
| Submerged Opening [inH₂O] | 8.3 | 9.8 |
| Submerged Closing [inH₂O] | 2.2 | 2.6 |
| Vertical Opening [inH₂O] | 16.5 | 17.7 |
| Vertical Closing [inH₂O] | 11.4 | 13.0 |

