


WASTOP® INLINE CHECK VALVE

WaStop 440

Model Name	WS440
Nominal Diameter	NPS 18
Fasteners mtrl.	AISI 316L
Gasket Mtrl.	EPDM
Weight [lb]	55.1
Max. ID Host Pipe [in]	18.3
Min. ID Host Pipe [in]	17.6
Max. Flow Vel. [fps]	9.8
Max. Flow Vol. [GPM]	7576.5

Product Variants

Art. No	WS440-S2-304/316	WS440-S3-304/316	WS440-S4-304/316
Membrane mtrl.	Polyurethane	Polyurethane	Polyurethane
Valve Body mtrl.	AISI 304 / AISI 316L	AISI 304 / AISI 316L	AISI 304 / AISI 316L
Max. Back Pressure [ftH2O]	9.8	16.4	26.2
Horizontal Opening [inH2O]	7.9	9.1	20.5
Horizontal Closing [inH ₂ O]	5.3	6.1	7.5
Submerged Opening [inH ₂ O]	4.9	5.7	6.5
Submerged Closing [inH ₂ O]	1.6	1.8	2.4
Vertical Opening [inH2O]	13.6	15.2	16.6
Vertical Closing [inH2O]	8.1	9.1	9.9



© 2024 Wapro AB. This document is subject to copyrights owned by Wapro AB. Any amendments, republication, retransmission, and/or reproduction of all or any part of the document is expressly prohibited, unless the copyright owner of the material has expressly granted its prior written consent. All other rights are reserved