

# WASTOP® INLINE CHECK VALVE

## WaStop 515

<b>Model Name</b>	WS515
<b>Nominal Diameter</b>	NPS 20
<b>Fasteners mtrl.</b>	AISI 316L
<b>Gasket Mtrl.</b>	EPDM
<b>Weight [lb]</b>	81.6
<b>Max. ID Host Pipe [in]</b>	21.1
<b>Min. ID Host Pipe [in]</b>	20.4
<b>Max. Flow Vel. [fps]</b>	13.1
<b>Max. Flow Vol. [GPM]</b>	13203.3

## Product Variants

Art. No	WS515-S3-304/316	WS515-S4-304/316
<b>Valve Body mtrl.</b>	AISI 304 / AISI 316L	AISI 304
<b>Max. Back Pressure [ftH<sub>2</sub>O]</b>	16.4	-
<b>Horizontal Opening [inH<sub>2</sub>O]</b>	10.7	14.2
<b>Horizontal Closing [inH<sub>2</sub>O]</b>	6.5	7.1
<b>Submerged Opening [inH<sub>2</sub>O]</b>	7.3	8.3
<b>Submerged Closing [inH<sub>2</sub>O]</b>	2.2	2.8
<b>Vertical Opening [inH<sub>2</sub>O]</b>	15.7	17.3
<b>Vertical Closing [inH<sub>2</sub>O]</b>	9.4	10.4

