

# WASTOP® INLINE CHECK VALVE

## WaStop 750

<b>Model Name</b>	WS750
<b>Nominal Diameter</b>	NPS 30
<b>Fasteners mtrl.</b>	AISI 316L
<b>Gasket Mtrl.</b>	EPDM
<b>Weight [lb]</b>	198.4
<b>Min. ID Host Pipe [in]</b>	29.7
<b>Max. ID Host Pipe [in]</b>	30.2
<b>Max. Flow Vel. [fps]</b>	13.1
<b>Max. Flow Vol. [GPM]</b>	28023.4

## Product Variants

Art. No	WS750-S2-304/316	WS750-S3-304/316	WS750-S4-304/316
<b>Valve Body mtrl.</b>	AISI 304 / AISI 316L	AISI 304 / AISI 316L	AISI 304 / AISI 316L
<b>Max. Back Pressure [ftH<sub>2</sub>O]</b>	9.8	16.4	26.2
<b>Horizontal Opening [inH<sub>2</sub>O]</b>	12.0	14.3	17.7
<b>Horizontal Closing [inH<sub>2</sub>O]</b>	7.5	8.6	10.6
<b>Submerged Opening [inH<sub>2</sub>O]</b>	7.3	8.5	9.6
<b>Submerged Closing [inH<sub>2</sub>O]</b>	2.4	2.8	3.5
<b>Vertical Opening [inH<sub>2</sub>O]</b>	16.7	18.5	20.4
<b>Vertical Closing [inH<sub>2</sub>O]</b>	7.1	7.9	8.7

