

# WASTOP® INLINE CHECK VALVE

## WaStop 885 Bell Bolt

<b>Model Name</b>	WS885-BB
<b>Nominal Diameter</b>	DN 900
<b>Fasteners mtrl.</b>	EN 1.4404
<b>Weight [kg]</b>	122
<b>Max. ID Host Pipe [mm]</b>	912
<b>Min. ID Host Pipe [mm]</b>	890
<b>Max. Flow Vel. [m/s]</b>	4
<b>Max. Flow Vol. [l/s]</b>	2546

## Product Variants

Art. No	WS885-S2-BB-304/316	WS885-S3-BB-304/316	WS885-S4-BB-304/316
<b>Membrane mtrl.</b>	Polyurethane	Polyurethane	Polyurethane
<b>Valve Body mtrl.</b>	EN 1.4404 / EN 1.4301	EN 1.4404 / EN 1.4301	EN 1.4404 / EN 1.4301
<b>Max. Back Pressure [mH<sub>2</sub>O]</b>	3	5	8
<b>Horizontal Opening [mmH<sub>2</sub>O]</b>	370	410	550
<b>Horizontal Closing [mmH<sub>2</sub>O]</b>	240	270	340
<b>Submerged Opening [mmH<sub>2</sub>O]</b>	215	245	275
<b>Submerged Closing [mmH<sub>2</sub>O]</b>	70	80	105
<b>Vertical Opening [mmH<sub>2</sub>O]</b>	455	505	555
<b>Vertical Closing [mmH<sub>2</sub>O]</b>	275	305	335

