



# WAREG® FLOW REGULATOR

## WaReg 200

|                               |                 |
|-------------------------------|-----------------|
| <b>Model Name</b>             | WR200-30        |
| <b>Nominal Diameter</b>       | NPS/OD 8        |
| <b>Bracket mtrl.</b>          | AISI 316L       |
| <b>Chamber mtrl.</b>          | PE              |
| <b>Connection pipe</b>        | 200 PE          |
| <b>Fasteners mtrl.</b>        | AISI 316L       |
| <b>Float mtrl.</b>            | PE              |
| <b>Flow Cap mtrl.</b>         | AISI 316L       |
| <b>Rubber joint mtrl.</b>     | EPDM            |
| <b>Spindle Mtrl.</b>          | Duplex SAF 2205 |
| <b>Spindle Nut Mtrl.</b>      | CuSn12          |
| <b>Minimum Sand Trap [in]</b> | 11.8            |
| <b>Weight [lb]</b>            | 701.1           |
| <b>Max. Flow Vol. [GPM]</b>   | 713.3           |
| <b>Min. Flow Vol. [GPM]</b>   | 348.7           |

## Product Variants

|   |                  |
|---|------------------|
| <b>Art. No</b>                              | <b>WR200-3.0</b> |
| <b>CO2 Equivalent (CO2e) [lb CO2e/unit]</b> | 933.1            |