

# WASTOP® INLINE CHECK VALVE

## WaStop 116

<b>Model Name</b>	WS116
<b>Nominal Diameter</b>	DN 125
<b>Fasteners mtrl.</b>	EN 1.4404
<b>Gasket Mtrl.</b>	EPDM
<b>Watertightness</b>	EN 13564
<b>Weight [kg]</b>	1.8
<b>Max. ID Host Pipe [mm]</b>	125
<b>Min. ID Host Pipe [mm]</b>	117
<b>Max. Flow Vel. [m/s]</b>	2
<b>Max. Flow Vol. [l/s]</b>	26

## Product Variants

Art. No	WS116-S2-316	WS116-S3-316	WS116-S4-316	WS116-C-316
<b>Membrane mtrl.</b>	MVQ Silicone	MVQ Silicone	MVQ Silicone	EPDM
<b>Valve Body mtrl.</b>	EN 1.4404	EN 1.4404	EN 1.4404	EN 1.4404
<b>Max. Back Pressure [mH<sub>2</sub>O]</b>	3	5	8	5
<b>Horizontal Opening [mmH<sub>2</sub>O]</b>	185	250	290	250
<b>Horizontal Closing [mmH<sub>2</sub>O]</b>	75	90	90	90
<b>Submerged Opening [mmH<sub>2</sub>O]</b>	175	200	225	180
<b>Submerged Closing [mmH<sub>2</sub>O]</b>	20	25	35	30
<b>Vertical Opening [mmH<sub>2</sub>O]</b>	215	255	285	280
<b>Vertical Closing [mmH<sub>2</sub>O]</b>	85	135	150	150

