

# WASTOP® INLINE CHECK VALVE

## WaStop 1185 Flange

<b>Model Name</b>	WS1185-FL
<b>Nominal Diameter</b>	NPS 48
<b>Fasteners mtrl.</b>	AISI 316L
<b>Flange Pattern</b>	wapro
<b>Weight [lb]</b>	859.8
<b>Min. ID Host Pipe [in]</b>	47.0
<b>Max. ID Host Pipe [in]</b>	48.4
<b>Max. Flow Vel. [fps]</b>	16.4
<b>Max. Flow Vol. [cfs]</b>	12.6

## Product Variants

Art. No	WS1185-S3-FL-304/316	WS1185-S4-FL-304/316
<b>Membrane mtrl.</b>	Polyurethane	Polyurethane
<b>Valve Body mtrl.</b>	AISI 316L / AISI 304	AISI 316L / AISI 304
<b>Max. Back Pressure [ftH<sub>2</sub>O]</b>	16.4	26.2
<b>Horizontal Opening [inH<sub>2</sub>O]</b>	17.2	21.1
<b>Horizontal Closing [inH<sub>2</sub>O]</b>	11.5	12.8
<b>Submerged Opening [inH<sub>2</sub>O]</b>	10.4	11.8
<b>Submerged Closing [inH<sub>2</sub>O]</b>	3.7	4.9

