

# WASTOP® PLASTIC SERIES

## WaStop 160 PVC

<b>Model Name</b>	WS160PVC
<b>Nominal Diameter</b>	DN/OD 160
<b>Fasteners mtrl.</b>	EN 1.4404
<b>Watertightness</b>	EN 13564
<b>Weight [kg]</b>	2
<b>Max. Flow Vel. [m/s]</b>	2
<b>Max. Flow Vol. [l/s]</b>	40

## Product Variants

Art. No	WS160PVC-S2	WS160PVC-S3	WS160PVC-S4
<b>Membrane mtrl.</b>	MVQ Silicone	MVQ Silicone	MVQ Silicone
<b>Valve Body mtrl.</b>	PVC	PVC	PVC
<b>Max. Back Pressure [mH<sub>2</sub>O]</b>	3	5	8
<b>Horizontal Opening [mmH<sub>2</sub>O]</b>	215	225	320
<b>Horizontal Closing [mmH<sub>2</sub>O]</b>	85	85	95
<b>Submerged Opening [mmH<sub>2</sub>O]</b>	155	180	190
<b>Submerged Closing [mmH<sub>2</sub>O]</b>	20	25	40
<b>Vertical Opening [mmH<sub>2</sub>O]</b>	235	265	290
<b>Vertical Closing [mmH<sub>2</sub>O]</b>	125	140	165

