

# WASTOP® INLINE CHECK VALVE

## WaStop 183

<b>Model Name</b>	WS183
<b>Nominal Diameter</b>	NPS 8
<b>Fasteners mtrl.</b>	AISI 316L
<b>Gasket Mtrl.</b>	EPDM
<b>Watertightness</b>	EN 13564
<b>Weight [lb]</b>	8.8
<b>Max. ID Host Pipe [in]</b>	7.9
<b>Min. ID Host Pipe [in]</b>	7.2
<b>Max. Flow Vel. [fps]</b>	6.6
<b>Max. Flow Vol. [GPM]</b>	1014.4

## Product Variants

Art. No	WS183-S2-316	WS183-S3-316	WS183-S4-316	WS183-C-316
<b>Membrane mtrl.</b>	MVQ Silicone	MVQ Silicone	MVQ Silicone	EPDM
<b>Valve Body mtrl.</b>	AISI 316L	AISI 316L	AISI 316L	AISI 316L
<b>Max. Back Pressure [ftH<sub>2</sub>O]</b>	9.8	16.4	26.2	16.4
<b>Horizontal Opening [inH<sub>2</sub>O]</b>	8.0	9.2	13.2	11.4
<b>Horizontal Closing [inH<sub>2</sub>O]</b>	3.6	4.0	6.1	3.9
<b>Submerged Opening [inH<sub>2</sub>O]</b>	6.9	7.9	8.9	7.9
<b>Submerged Closing [inH<sub>2</sub>O]</b>	1.2	1.4	1.8	1.4
<b>Vertical Opening [inH<sub>2</sub>O]</b>	10.4	12.4	13.7	12.4
<b>Vertical Closing [inH<sub>2</sub>O]</b>	6.5	11.2	12.4	11.2

