

WASTOP® PLASTIC SERIES

WaStop 200 PVC

Model Name	WS200PVC
Nominal Diameter	NPS/OD 8
Fasteners mtrl.	AISI 316L
Watertightness	EN 13564
Weight [lb]	8.2
Max. Flow Vel. [fps]	6.6
Max. Flow Vol. [GPM]	998.6

Product Variants

Art. No	WS200PVC-S2	WS200PVC-S3	WS200PVC-S4	WS200PVC-C
Membrane mtrl.	MVQ Silicone	MVQ Silicone	MVQ Silicone	EPDM
Valve Body mtrl.	PVC	PVC	PVC	PVC
Max. Back Pressure [ftH ₂ O]	9.8	16.4	26.2	16.4
Horizontal Opening [inH ₂ O]	8.5	9.3	12.4	8.3
Horizontal Closing [inH ₂ O]	4.6	4.8	6.5	4.3
Submerged Opening [inH ₂ O]	5.9	6.7	7.5	6.7
Submerged Closing [inH ₂ O]	1.2	1.4	1.8	1.4
Vertical Opening [inH ₂ O]	10.6	11.6	12.9	11.6
Vertical Closing [inH ₂ O]	6.1	7.1	7.8	7.1

WS200PVC-S3 Open Air Submerged Outlet Without WaStop 2.5 2.0 Head loss [ftH₂O] 1.5 1.0 0.5 0.0 0 800 1000 200 400 600 Flow [GPM]

© 2025 Wapro AB. This document is subject to copyrights owned by Wapro AB. Any amendments, republication, retransmission, and/or reproduction of all or any part of the document is expressly prohibited, unless the copyright owner of the material has expressly granted its prior written consent. All other rights are reserved

Wapro AB Munkahusvägen 103 SE-37431 Karlshamn +46 (0)454 185 10 wapro@wapro.com HOLDING BACK

THE FLOOD