

# WASTOP® INLINE CHECK VALVE

## WaStop 230

<b>Model Name</b>	WS230
<b>Nominal Diameter</b>	DN 250
<b>Fasteners mtrl.</b>	EN 1.4404
<b>Gasket Mtrl.</b>	EPDM
<b>Weight [kg]</b>	6.7
<b>Min. ID Host Pipe [mm]</b>	232
<b>Max. ID Host Pipe [mm]</b>	248
<b>Max. Flow Vel. [m/s]</b>	2
<b>Max. Flow Vol. [l/s]</b>	100

## Product Variants

<b>Art. No</b>	<b>WS230-S3-316</b>
<b>Membrane mtrl.</b>	EPDM
<b>Valve Body mtrl.</b>	EN 1.4404
<b>Max. Back Pressure [mH<sub>2</sub>O]</b>	5
<b>Horizontal Opening [mmH<sub>2</sub>O]</b>	200
<b>Horizontal Closing [mmH<sub>2</sub>O]</b>	115
<b>Submerged Opening [mmH<sub>2</sub>O]</b>	165
<b>Submerged Closing [mmH<sub>2</sub>O]</b>	45
<b>Vertical Opening [mmH<sub>2</sub>O]</b>	285
<b>Vertical Closing [mmH<sub>2</sub>O]</b>	170

