

# WASTOP® INLINE CHECK VALVE

## WaStop 230

|                               |           |
|-------------------------------|-----------|
| <b>Model Name</b>             | WS230     |
| <b>Nominal Diameter</b>       | NPS 10    |
| <b>Fasteners mtrl.</b>        | AISI 316L |
| <b>Gasket Mtrl.</b>           | EPDM      |
| <b>Weight [lb]</b>            | 14.8      |
| <b>Min. ID Host Pipe [in]</b> | 9.1       |
| <b>Max. ID Host Pipe [in]</b> | 9.8       |
| <b>Max. Flow Vel. [fps]</b>   | 6.6       |
| <b>Max. Flow Vol. [GPM]</b>   | 1585.0    |

## Product Variants

|  |                     |
|--|---------------------|
| <b>Art. No</b>                               | <b>WS230-S3-316</b> |
| <b>Membrane mtrl.</b>                        | EPDM                |
| <b>Valve Body mtrl.</b>                      | AISI 316L           |
| <b>Max. Back Pressure [ftH<sub>2</sub>O]</b> | 16.4                |
| <b>Horizontal Opening [inH<sub>2</sub>O]</b> | 7.9                 |
| <b>Horizontal Closing [inH<sub>2</sub>O]</b> | 4.5                 |
| <b>Submerged Opening [inH<sub>2</sub>O]</b>  | 6.5                 |
| <b>Submerged Closing [inH<sub>2</sub>O]</b>  | 1.8                 |
| <b>Vertical Opening [inH<sub>2</sub>O]</b>   | 11.2                |
| <b>Vertical Closing [inH<sub>2</sub>O]</b>   | 6.7                 |

