

WASTOP® INLINE CHECK VALVE

WaStop 240

| | |
|-------------------------------|-----------|
| Model Name | WS240 |
| Nominal Diameter | NPS 10 |
| Fasteners mtrl. | AISI 316L |
| Gasket Mtrl. | EPDM |
| Weight [lb] | 14.8 |
| Min. ID Host Pipe [in] | 9.5 |
| Max. ID Host Pipe [in] | 10.2 |
| Max. Flow Vel. [fps] | 6.6 |
| Max. Flow Vol. [GPM] | 1585.0 |

Product Variants

| Art. No | WS240-S3-316 | WS240-S4-316 |
|--|--------------|--------------|
| Membrane mtrl. | Polyurethane | Polyurethane |
| Valve Body mtrl. | AISI 316L | AISI 316L |
| Max. Back Pressure [ftH₂O] | 16.4 | 26.2 |
| Horizontal Opening [inH₂O] | 8.1 | 13.8 |
| Horizontal Closing [inH₂O] | 4.7 | 4.3 |
| Submerged Opening [inH₂O] | 4.9 | 12.2 |
| Submerged Closing [inH₂O] | 1.4 | 2.6 |
| Vertical Opening [inH₂O] | 12.6 | 13.6 |
| Vertical Closing [inH₂O] | 7.9 | 7.9 |

