

WASTOP® BACKVENTIL

WaStop 101

Modellnamn	WS101
Nominell Diameter	DN 100
Packning	EPDM
Skruvmaterial	EN 1.4404
Vattentäthet	EN 13564
Vikt [kg]	0.9
Max. flödeshastighet [m/s]	2
Max. flödesvolym [l/s]	20
Min. ID Installationsrör [mm]	101
Max. ID Installationsrör [mm]	111

Produktvarianter

Art.nr	WS101-S2-316	WS101-S3-316	WS101-S4-316	WS101-C-316
Membranmtrl.	MVQ Silicone	MVQ Silicone	MVQ Silicone	EPDM
Ventilkropp	EN 1.4404	EN 1.4404	EN 1.4404	EN 1.4404
Horisontell Öppning [mmH ₂ O]	165	185	245	180
Horisontell Stängning [mmH ₂ O]	65	70	75	80
Nedsänkt Öppning [mmH ₂ O]	135	155	175	140
Nedsänkt Stängning [mmH ₂ O]	15	20	25	15
Vertikal Öppning [mmH ₂ O]	210	250	275	230
Vertikal Stängning [mmH ₂ O]	80	90	100	120
CO ₂ -ekvivalent (CO ₂ e) [kg CO ₂ e/unit]	14.1	14.2	-	15
Max. baktryck [mH ₂ O]	3	5	8	5

