

## WASTOP® PLASTIC SERIES

## WaStop 110 PVC

Model Name	WS110PVC
Nominal Diameter	DN/OD 110
Fasteners mtrl.	EN 1.4404
Watertightness	EN 13564
Weight [kg]	0.7
Max. Flow Velocity [m/s]	2
Max. Flow Volume [l/s]	19

## **Product Variants**

Art. No	WS110PVC-S2	WS110PVC-S3	WS110PVC-S4	WS110PVC-C
Membrane mtrl.	MVQ Silicone	MVQ Silicone	MVQ Silicone	EPDM
Valve Body	PVC	PVC	PVC	PVC
Max. Back Pressure [mH <sub>2</sub> O]	3	5	8	5
Horizontal Opening [mmH <sub>2</sub> O]	170	185	240	180
Horizontal Closing [mmH <sub>2</sub> O]	70	70	80	80
Submerged Opening [mmH <sub>2</sub> O]	135	155	175	140
Submerged Closing [mmH <sub>2</sub> O]	15	20	25	15
Vertical Opening [mmH <sub>2</sub> O]	210	250	275	230
Vertical Closing [mmH <sub>2</sub> O]	80	90	100	120

WS110PVC-S3 0.8 Open Air Submerged Outlet Without WaStop 0.7 0.6 Head loss [mH<sub>2</sub>0] 0.5 0.4 0.3 0.2 0.1 0.0 2.5 5.0 7.5 10.0 12.5 15.0 17.5 0.0 Flow [//s]

© 2025 Wapro AB. This document is subject to copyrights owned by Wapro AB. Any amendments, republication, retransmission, and/or reproduction of all or any part of the document is expressly prohibited, unless the copyright owner of the material has expressly granted its prior written consent. All other rights are reserved

+46 (0)454 185 10 wapro@wapro.com