

WASTOP® BACKVENTIL

WaStop 116

Modellnamn	WS116
Nominell Diameter	DN 125
Packning	EPDM
Skruvmaterial	EN 1.4404
Vattentäthet	EN 13564
Vikt [kg]	1.8
Max. flödeshastighet [m/s]	2
Max. flödesvolym [l/s]	26
Max. ID Installationsrör [mm]	125
Min. ID Installationsrör [mm]	117

Produktvarianter

Art.nr	WS116-S2-316	WS116-S3-316	WS116-S4-316	WS116-C-316
Membranmtrl.	MVQ Silicone	MVQ Silicone	MVQ Silicone	EPDM
Ventilkropp	EN 1.4404	EN 1.4404	EN 1.4404	EN 1.4404
Horisontell Öppning [mmH ₂ O]	185	250	290	250
Horisontell Stängning [mmH ₂ O]	75	90	90	90
Nedsänkt Öppning [mmH ₂ O]	175	200	225	180
Nedsänkt Stängning [mmH ₂ O]	20	25	35	30
Vertikal Öppning [mmH ₂ O]	215	255	285	280
Vertikal Stängning [mmH ₂ O]	85	135	150	150
CO ₂ -ekvivalent (CO ₂ e) [kg CO ₂ e/unit]	15	15.2	15.5	-
Max. baktryck [mH ₂ O]	3	5	8	5

