

WASTOP® BACKVENTIL

WaStop 146

Modellnamn	WS146
Nominell Diameter	DN 150
Packning	EPDM
Skruvmaterial	EN 1.4404
Vattentäthet	EN 13564
Vikt [kg]	2.6
Max. flödeshastighet [m/s]	2
Max. flödesvolym [l/s]	36
Min. ID Installationsrör [mm]	146
Max. ID Installationsrör [mm]	159

Produktvarianter

Art.nr	WS146-S2-316	WS146-S3-316	WS146-S4-316
Membranmtrl.	MVQ Silicone	MVQ Silicone	MVQ Silicone
Ventilkropp	EN 1.4404	EN 1.4404	EN 1.4404
Horisontell Öppning [mmH ₂ O]	200	230	335
Horisontell Stängning [mmH ₂ O]	75	80	105
Nedsänkt Öppning [mmH ₂ O]	150	175	200
Nedsänkt Stängning [mmH ₂ O]	20	25	35
Vertikal Öppning [mmH ₂ O]	240	350	385
Vertikal Stängning [mmH ₂ O]	110	120	130
CO ₂ -ekvivalent (CO ₂ e) [kg CO ₂ e/unit]	23.2	23.2	-
Max. baktryck [mH ₂ O]	3	5	8

