


WASTOP® INLINE CHECK VALVE

WaStop 183

Model Name	WS183
Nominal Diameter	NPS 8
Fasteners mtrl.	AISI 316L
Gasket	EPDM
Watertightness	EN 13564
Weight [lb]	8.8
Max. ID Host Pipe [in]	7.9
Min. ID Host Pipe [in]	7.2
Max. Flow Velocity [fps]	6.6
Max. Flow Volume [GPM]	1014.4

Product Variants

Art. No	WS183-S2-316	WS183-S3-316	WS183-S4-316	WS183-C-316	
Membrane mtrl.	MVQ Silicone	MVQ Silicone	MVQ Silicone	EPDM	
Valve Body	AISI 316L	AISI 316L	AISI 316L	AISI 316L	
Max. Back Pressure [ftH ₂ O]	9.8	16.4	26.2	16.4	
Horizontal Opening [inH2O]	8.0	9.2	13.2	11.4	
Horizontal Closing [inH2O]	3.6	4.0	6.1	3.9	
Submerged Opening [inH2O]	6.9	7.9	8.9	7.9	
Submerged Closing [inH2O]	1.2	1.4	1.8	1.4	
Vertical Opening [inH2O]	10.4	12.4	13.7	12.4	
Vertical Closing [inH2O]	6.5	11.2	12.4	11.2	
CO ₂ Equivalent (CO ₂ e) [lb CO ₂ e/unit]	70.8	71.0	-	-	



© 2025 Wapro AB. This document is subject to copyrights owned by Wapro AB. Any amendments, republication, retransmission, and/or reproduction of all or any part of the document is expressly prohibited, unless the copyright owner of the material has expressly granted its prior written consent. All other rights are reserved