

WASTOP® BACKVENTIL

WaStop 183

Modellnamn	WS183
Nominell Diameter	DN 200
Packning	EPDM
Skruvmaterial	EN 1.4404
Vattentäthet	EN 13564
Vikt [kg]	4
Max. flödeshastighet [m/s]	2
Max. flödesvolym [l/s]	64
Max. ID Installationsrör [mm]	200
Min. ID Installationsrör [mm]	182

Produktvarianter

Art.nr	WS183-S2-316	WS183-S3-316	WS183-S4-316	WS183-C-316
Membranmtrl.	MVQ Silicone	MVQ Silicone	MVQ Silicone	EPDM
Ventilkropp	EN 1.4404	EN 1.4404	EN 1.4404	EN 1.4404
Horisontell Öppning [mmH ₂ O]	205	235	335	290
Horisontell Stängning [mmH ₂ O]	90	100	155	100
Nedsänkt Öppning [mmH ₂ O]	175	200	225	200
Nedsänkt Stängning [mmH ₂ O]	30	35	45	35
Vertikal Öppning [mmH ₂ O]	265	315	350	315
Vertikal Stängning [mmH ₂ O]	165	285	315	285
CO ₂ -ekvivalent (CO ₂ e) [kg CO ₂ e/unit]	32.1	32.2	-	-
Max. baktryck [mH ₂ O]	3	5	8	5

