

WASTOP® BACKVENTIL

WaStop 193

Modellnamn	WS193
Nominell Diameter	DN 200
Packning	EPDM
Skruvmaterial	EN 1.4404
Vattentäthet	EN 13564
Vikt [kg]	4.3
Max. flödeshastighet [m/s]	2
Max. flödesvolym [l/s]	64
Max. ID Installationsrör [mm]	209
Min. ID Installationsrör [mm]	192

Produktvarianter

Art.nr	WS193-S2-316	WS193-S3-316	WS193-S4-316
Membranmtrl.	MVQ Silicone	MVQ Silicone	MVQ Silicone
Ventilkropp	EN 1.4404	EN 1.4404	EN 1.4404
Horisontell Öppning [mmH ₂ O]	210	235	315
Horisontell Stängning [mmH ₂ O]	105	120	165
Nedsänkt Öppning [mmH ₂ O]	150	170	190
Nedsänkt Stängning [mmH ₂ O]	30	35	45
Vertikal Öppning [mmH ₂ O]	270	295	325
Vertikal Stängning [mmH ₂ O]	155	180	200
CO ₂ -ekvivalent (CO ₂ e) [kg CO ₂ e/unit]	33.6	33.7	33.9
Max. baktryck [mH ₂ O]	3	5	8

