



# WASTOP® INLINE CHECK VALVE

## WaStop 230

|                          |           |
|--------------------------|-----------|
| Model Name               | WS230     |
| Nominal Diameter         | DN 250    |
| Fasteners mtrl.          | EN 1.4404 |
| Gasket                   | EPDM      |
| Weight [kg]              | 6.7       |
| Min. ID Host Pipe [mm]   | 232       |
| Max. ID Host Pipe [mm]   | 248       |
| Max. Flow Velocity [m/s] | 2         |
| Max. Flow Volume [l/s]   | 100       |

## Product Variants

|                                                                            |              |
|----------------------------------------------------------------------------|--------------|
| Art. No                                                                    | WS230-S3-316 |
| Membrane mtrl.                                                             | EPDM         |
| Valve Body                                                                 | EN 1.4404    |
| Max. Back Pressure [mH <sub>2</sub> O]                                     | 5            |
| Horizontal Opening [mmH <sub>2</sub> O]                                    | 200          |
| Horizontal Closing [mmH <sub>2</sub> O]                                    | 115          |
| Submerged Opening [mmH <sub>2</sub> O]                                     | 165          |
| Submerged Closing [mmH <sub>2</sub> O]                                     | 45           |
| Vertical Opening [mmH <sub>2</sub> O]                                      | 285          |
| Vertical Closing [mmH <sub>2</sub> O]                                      | 170          |
| CO <sub>2</sub> Equivalent (CO <sub>2</sub> e) [kg CO <sub>2</sub> e/unit] | 41.2         |

