

WASTOP® BACKVENTIL

WaStop 490

Modellnamn	WS490
Nominell Diameter	DN 500
Packning	EPDM
Skruvmaterial	EN 1.4404
Vikt [kg]	32
Max. flödeshastighet [m/s]	4
Max. flödesvolym [l/s]	786
Max. ID Installationsrör [mm]	511
Min. ID Installationsrör [mm]	493

Produktvarianter

Art.nr	WS490-S2-304/316	WS490-S3-304/316	WS490-S4-304/316
Membranmtrl.	Polyuretan	Polyuretan	Polyuretan
Ventilkropp	EN 1.4301 / EN 1.4404	EN 1.4301 / EN 1.4404	EN 1.4301 / EN 1.4404
Horisontell Öppning [mmH ₂ O]	230	250	260
Horisontell Stängning [mmH ₂ O]	140	160	165
Nedsänkt Öppning [mmH ₂ O]	160	185	210
Nedsänkt Stängning [mmH ₂ O]	50	55	70
Vertikal Öppning [mmH ₂ O]	360	400	435
Vertikal Stängning [mmH ₂ O]	215	240	260
CO ₂ -ekvivalent (CO ₂ e) [kg CO ₂ e/unit]	170.3	179.8	-
Max. baktryck [mH ₂ O]	3	5	8

