

WASTOP® BACKVENTIL

WaStop 690

Modellnamn	WS690
Nominell Diameter	DN 700
Packning	EPDM
Skruvmaterial	EN 1.4404
Vikt [kg]	73
Max. flödeshastighet [m/s]	4
Max. flödesvolym [m³/s]	1.54
Min. ID Installationsrör [mm]	692
Max. ID Installationsrör [mm]	710

Produktvarianter

Art.nr	WS690-S2-304/316	WS690-S3-304/316	WS690-S4-304/316
Membranmtrl.	Polyuretan	Polyuretan	Polyuretan
Ventilkropp	EN 1.4301 / EN 1.4404	EN 1.4301 / EN 1.4404	EN 1.4301 / EN 1.4404
Horisontell Öppning [mmH ₂ O]	215	265	280
Horisontell Stängning [mmH ₂ O]	135	170	175
Nedsänkt Öppning [mmH ₂ O]	140	160	180
Nedsänkt Stängning [mmH ₂ O]	40	45	60
Vertikal Öppning [mmH ₂ O]	405	450	495
Vertikal Stängning [mmH ₂ O]	245	275	300
CO ₂ -ekvivalent (CO ₂ e) [kg CO ₂ e/unit]	327.4	374.8	-
Max. baktryck [mH ₂ O]	3	5	8

