



WASTOP® PLASTIC SERIES

WaStop 75 PVC

| | |
|----------------------|-----------|
| Model Name | WS75PVC |
| Nominal Diameter | NPS/OD 3 |
| Fasteners mtrl. | AISI 316L |
| Watertightness | EN 13564 |
| Weight [lb] | 0.7 |
| Max. Flow Vel. [fps] | 6.6 |
| Max. Flow Vol. [GPM] | 142.7 |

Product Variants

| Art. No | WS75PVC-S3 | WS75PVC-S4 | WS75PVC-C |
|---|--------------|--------------|-----------|
| Membrane mtrl. | MVQ Silicone | MVQ Silicone | EPDM |
| Valve Body mtrl. | PVC | PVC | PVC |
| Max. Back Pressure [ftH ₂ O] | 16.4 | 26.2 | 16.4 |
| Horizontal Opening [inH ₂ O] | 9.8 | 11.0 | 11.2 |
| Horizontal Closing [inH ₂ O] | 4.1 | 5.3 | 5.5 |
| Submerged Opening [inH ₂ O] | 5.9 | 7.1 | 7.5 |
| Submerged Closing [inH ₂ O] | 2.4 | 3.5 | 4.3 |
| Vertical Opening [inH ₂ O] | 8.9 | 10.0 | 10.2 |
| Vertical Closing [inH ₂ O] | 2.4 | 3.5 | 3.9 |

