



# WASTOP® INLINE CHECK VALVE

## WaStop 370 One Collar

Model Name	WS370-OC
Nominal Diameter	DN 370
Fasteners mtrl.	EN 1.4404
Gasket	EPDM
Weight [kg]	19
Max. ID Host Pipe [mm]	390
Min. ID Host Pipe [mm]	361
Max. Flow Velocity [m/s]	3
Max. Flow Volume [l/s]	378

### Product Variants

Art. No	WS370-S3-316-OC	WS370-S4-316-OC
Membrane mtrl.	Polyurethane	Polyurethane
Valve Body	EN 1.4404	EN 1.4404
Max. Back Pressure [mH <sub>2</sub> O]	5	8
Horizontal Opening [mmH <sub>2</sub> O]	255	330
Horizontal Closing [mmH <sub>2</sub> O]	160	200
Submerged Opening [mmH <sub>2</sub> O]	140	190
Submerged Closing [mmH <sub>2</sub> O]	45	80
Vertical Opening [mmH <sub>2</sub> O]	360	330
Vertical Closing [mmH <sub>2</sub> O]	210	190
CO <sub>2</sub> Equivalent (CO <sub>2</sub> e) [kg CO <sub>2</sub> e/unit]	108.3	112.3
Weight [kg]	18.2	19.4

