



# WASTOP® INLINE CHECK VALVE

## WaStop 370

Model Name	WS370
Nominal Diameter	NPS 15
Fasteners mtrl.	AISI 316L
Gasket	EPDM
Weight [lb]	41.9
Min. ID Host Pipe [in]	14.7
Max. ID Host Pipe [in]	15.4
Max. Flow Velocity [fps]	9.8
Max. Flow Volume [GPM]	5991.4

## Product Variants

Art. No	WS370-S3-316	WS370-S4-316
Membrane mtrl.	Polyurethane	Polyurethane
Valve Body	AISI 316L	AISI 316L
Max. Back Pressure [ftH <sub>2</sub> O]	16.4	26.2
Horizontal Opening [inH <sub>2</sub> O]	10.0	13.0
Horizontal Closing [inH <sub>2</sub> O]	6.2	7.9
Submerged Opening [inH <sub>2</sub> O]	5.5	7.5
Submerged Closing [inH <sub>2</sub> O]	1.8	3.1
Vertical Opening [inH <sub>2</sub> O]	14.2	13.0
Vertical Closing [inH <sub>2</sub> O]	8.3	7.5
CO <sub>2</sub> Equivalent (CO <sub>2</sub> e) [lb CO <sub>2</sub> e/unit]	243.6	260.8
Weight [lb]	41.1	44.4

