



WASTOP® INLINE CHECK VALVE

WaStop 750

Model Name	WS750
Nominal Diameter	DN 750
Fasteners mtrl.	EN 1.4404
Gasket	EPDM
Weight [kg]	90
Min. ID Host Pipe [mm]	755
Max. ID Host Pipe [mm]	767
Max. Flow Velocity [m/s]	4
Max. Flow Volume [m³/s]	1.77

Product Variants

Art. No	WS750-S2-304/316	WS750-S3-304/316	WS750-S4-304/316
Membrane mtrl.	Polyurethane	Polyurethane	Polyurethane
Valve Body	EN 1.4301 / EN 1.4404	EN 1.4301 / EN 1.4404	EN 1.4301 / EN 1.4404
Max. Back Pressure [mH ₂ O]	3	5	8
Horizontal Opening [mmH ₂ O]	305	365	450
Horizontal Closing [mmH ₂ O]	190	220	270
Submerged Opening [mmH ₂ O]	185	215	245
Submerged Closing [mmH ₂ O]	60	70	90
Vertical Opening [mmH ₂ O]	425	470	515
Vertical Closing [mmH ₂ O]	180	200	220
CO ₂ Equivalent (CO ₂ e) [kg CO ₂ e/unit]	-	448.8	-

