



WASTOP® INLINE CHECK VALVE

WaStop 885

Model Name	WS885
Nominal Diameter	DN 900
Fasteners mtrl.	EN 1.4404
Gasket	EPDM
Weight [kg]	116
Max. ID Host Pipe [mm]	912
Min. ID Host Pipe [mm]	890
Max. Flow Velocity [m/s]	4
Max. Flow Volume [m³/s]	2.55

Product Variants

Art. No	WS885-S2-304/316	WS885-S3-304/316	WS885-S4-304/316
Membrane mtrl.	Polyurethane	Polyurethane	Polyurethane
Valve Body	EN 1.4301 / EN 1.4404	EN 1.4301 / EN 1.4404	EN 1.4301 / EN 1.4404
Max. Back Pressure [mH ₂ O]	3	5	8
Horizontal Opening [mmH ₂ O]	370	410	550
Horizontal Closing [mmH ₂ O]	240	270	340
Submerged Opening [mmH ₂ O]	215	245	275
Submerged Closing [mmH ₂ O]	70	80	105
Vertical Opening [mmH ₂ O]	455	505	555
Vertical Closing [mmH ₂ O]	275	305	335
CO ₂ Equivalent (CO ₂ e) [kg CO ₂ e/unit]	-	661.7	-

