


WASTOP® INLINE CHECK VALVE

WaStop 1185 Flange

Model Name	WS1185-FL
Nominal Diameter	NPS 48
Fasteners mtrl.	AISI 316L
Flange bolt pattern	wapro
Weight [lb]	859.8
Min. ID Host Pipe [in]	47.0
Max. ID Host Pipe [in]	48.4
Max. Flow Velocity [fps]	16.4
Max. Flow Volume [cfs]	199.67

Product Variants

Art. No	WS1185-S3-FL-304/316	WS1185-S4-FL-304/316
Membrane mtrl.	Polyurethane	Polyurethane
Valve Body	AISI 316L / AISI 304	AISI 316L / AISI 304
Max. Back Pressure [ftH ₂ O]	16.4	26.2
Horizontal Opening [inH ₂ O]	17.2	21.1
Horizontal Closing [inH ₂ O]	11.5	12.8
Submerged Opening [inH ₂ O]	10.4	11.8
Submerged Closing [inH ₂ O]	3.7	4.9
Vertical Opening [inH ₂ O]	22.8	27.8
Vertical Closing [inH ₂ O]	16.9	19.5
CO ₂ Equivalent (CO ₂ e) [lb CO ₂ e/unit]	3876.0	-



© 2025 Wapro AB. This document is subject to copyrights owned by Wapro AB. Any amendments, republication, retransmission, and/or reproduction of all or any part of the document is expressly prohibited, unless the copyright owner of the material has expressly granted its prior written consent. All other rights are reserved