



WASTOP® INLINE CHECK VALVE

WaStop 750

Model Name	WS750
Nominal Diameter	NPS 30
Fasteners mtrl.	AISI 316L
Gasket	EPDM
Weight [lb]	198.4
Min. ID Host Pipe [in]	29.7
Max. ID Host Pipe [in]	30.2
Max. Flow Velocity [fps]	13.1
Max. Flow Volume [cfs]	62.44

Product Variants

Art. No	WS750-S2-304/316	WS750-S3-304/316	WS750-S4-304/316
Membrane mtrl.	Polyurethane	Polyurethane	Polyurethane
Valve Body	AISI 316L / AISI 304	AISI 316L / AISI 304	AISI 316L / AISI 304
Max. Back Pressure [ftH ₂ O]	9.8	16.4	26.2
Horizontal Opening [inH ₂ O]	12.0	14.3	17.7
Horizontal Closing [inH ₂ O]	7.5	8.6	10.6
Submerged Opening [inH ₂ O]	7.3	8.5	9.6
Submerged Closing [inH ₂ O]	2.4	2.8	3.5
Vertical Opening [inH ₂ O]	16.7	18.5	20.4
Vertical Closing [inH ₂ O]	7.1	7.9	8.7
CO ₂ Equivalent (CO ₂ e) [lb CO ₂ e/unit]	992.7 / 994.1	988.3 / 989.4	992.5 / 989.7
Weight [lb]	201.0	199.7	199.7

