



WASTOP® INLINE CHECK VALVE

WaStop 885 Short

Model Name	WS885-SH
Nominal Diameter	NPS 36
Fasteners mtrl.	AISI 316L
Gasket	EPDM
Weight [lb]	235.9
Min. ID Host Pipe [in]	35.0
Max. ID Host Pipe [in]	35.9
Max. Flow Velocity [fps]	13.1
Max. Flow Volume [cfs]	89.91

Product Variants

Art. No	WS885-S2-SH-304/316	WS885-S3-SH-304/316	WS885-S4-SH-304/316
Membrane mtrl.	Polyurethane	Polyurethane	Polyurethane
Valve Body	AISI 304 / AISI 316L	AISI 304 / AISI 316L	AISI 304
Max. Back Pressure [ftH ₂ O]	9.8	9.8	9.8
Horizontal Opening [inH ₂ O]	14.6	16.1	21.7
Horizontal Closing [inH ₂ O]	9.4	10.6	13.4
Submerged Opening [inH ₂ O]	8.5	9.6	10.8
Submerged Closing [inH ₂ O]	2.8	3.1	4.1
Vertical Opening [inH ₂ O]	17.9	19.9	21.9
Vertical Closing [inH ₂ O]	10.8	12.0	13.3

