



WASTOP® INLINE CHECK VALVE

WaStop 116

Model Name	WS116
Nominal Diameter	DN 125
Fasteners mtrl.	EN 1.4404
Gasket	EPDM
Watertightness	EN 13564
Weight [kg]	1.8
Max. ID Host Pipe [mm]	125
Min. ID Host Pipe [mm]	117
Max. Flow Velocity [m/s]	2
Max. Flow Volume [l/s]	26

Product Variants

Art. No	WS116-S2-316	WS116-S3-316	WS116-S4-316	WS116-C-316
Membrane mtrl.	MVQ Silicone	MVQ Silicone	MVQ Silicone	EPDM
Valve Body	EN 1.4404	EN 1.4404	EN 1.4404	EN 1.4404
Max. Back Pressure [mH ₂ O]	3	5	8	5
Horizontal Opening [mmH ₂ O]	185	250	290	250
Horizontal Closing [mmH ₂ O]	75	90	90	90
Submerged Opening [mmH ₂ O]	175	200	225	180
Submerged Closing [mmH ₂ O]	20	25	35	30
Vertical Opening [mmH ₂ O]	215	255	285	280
Vertical Closing [mmH ₂ O]	85	135	150	150
CO ₂ Equivalent (CO ₂ e) [kg CO ₂ e/unit]	15	15.2	15.5	-
Weight [kg]	1	1	1	-

